




# FLEXIGOM<sup>®</sup> EXTRA



## Performance

- Excellent resistance to abrasion and intensive use by professionals.
- Highly resistant to oil, gasoline and a wide range of chemicals.
- Very resistant to both contact and radiant heat.
- Light and flexible hose even at low temperatures (-15°C). Easy to handle and roll up.
- Highly resistant to breakage thanks to the specially-made textile.
- No maintenance or drying necessary.

## Uses

- Agriculture.
- Industry.

## Construction

### **Interior and exterior layer:**


Specially-formulated black nitrile rubber, extruded through the circular fabric. Minimal flow loss thanks to its smooth interior wall. Outer grooves to improve resistance to abrasion and ease of use.

### **Reinforced middle textile:**

Heavy duty circular weaved outer layer made from high tenacity polyester thread. No defects (broken threads, knots, etc.)



# FLEXIGOM<sup>®</sup> EXTRA



## Technical characteristics

DIAMETER		WEIGHT	THICKNESS	WORKING PRESSURE	BREAKAGE PRESSURE
INCHES	MM.	GR/M.	MM.	BARS	BARS
2"	52	565	2,70	20	>60
2 <sup>1/2</sup> "	64	720	3,00	17	>52
3"	75	1.020	3,30	17	>50
3 <sup>1/2</sup> "	90	1.115	3,30	15	>45
4"	102	1.300	3,10	17	>52
4 <sup>1/2</sup> "	115	1.450	3,10	15	>45
5"	125	1.660	3,10	15	>45
6"	152	2.300	3,30	15	>45