

ATLAS[®]-C SUPRA

CONSTRUCTION

Interior lining:

Special lining made from thermoplastic synthetic materials. Minimal flow loss thanks to its smooth walls.

Exterior fabric:

Circular weaved outer layer made from high tenacity polyester thread. Flat fabric used as the standard, twill option with a minimum order. No defects (broken threads, knots, etc.)

Exterior permeation:

Red PU-based emulsion as standard (other colours with a minimum order).

PERFORMANCE

- Highly resistant to abrasion and intensive use by professionals.
- Very light and flexible hose.
- Easy to handle and roll up.
- Resistant to pressure thanks to its circular weave construction.
- Options for PU and/or synthetic rubber interior lining.
- Highly resistant to ozone thanks to its outer coating that also improves abrasion.
- Personalised markings with a minimum order.
- Available with various international certifications.

APPLICATIONS

- Fire-fighters and Industry.
- Construction.
- Refineries.
- Military.
- Airports.
- Oil tankers and platforms.

TECHNICAL CHARACTERISTICS

DIAMETER		WEIGHT	WORKING PRESSURE	TEST PRESSURE	BURST PRESSURE
inches	mm.	gr/m.	Bars	Bars	Bars
1¾"	45	245	17	34	>50
2¾"	70	460	17	34	>90